



- ① FINISH GRADE OR TOP OF MULCH
- ② PLANT MATERIAL (SHRUB OR GROUND COVER)
- ③ CLEAN SOIL, AMENDED/NATIVE – FREE OF ROCK AND DEBRIS
- ④ VARI-ROTOR SPRAY 10-32 UNF THREAD (ANTELCO). MOUNT ON ASTA STAKE, SEE LEGEND FOR SIZE.
- ⑤ ASTA STAKE ADAPTER, 0.16 F x 0.18" BARB (ANTELCO #41005).
- ⑥ 1/4" DISTRIBUTION TUBING VINYL (ANTELCO) LENGTH AS NEEDED.
- ⑦ JOINER 0.16", BARBxBARB, (ANTELCO #40935 or #40145).
- ⑧ POLYETHYLENE PIPE, LLDPE. SIZE PER PLANS.
- ⑨ ASTA STAKE HOLD-DOWN #43615.
- ⑩ ASTA STAKE (ANTELCO) SEE LEGEND FOR SIZE AND MODEL #.

NOTE:
 SET ZONE PRESSURE TO 30
 PSI. ADJUST VARI-ROTOR
 SPRAY DIAMETER AS NEEDED.

NOTE:
 ANTELCO VARI-ROTOR SPRAY
 SPECIFICATIONS:

ARC	MOD#	DIAMETER	GPH	@	PSI
360°	CIR 20205	0-27-FT	0-33.0	@	30

00

ANTELCO VARI-ROTOR SPRAY™ ON ASTA® STAKE

N.T.S.

DETAIL-FILE