



- ① FINISH GRADE OR TOP OF MULCH
- ② PLANT MATERIAL (SHRUB OR GROUND COVER)
- ③ CLEAN SOIL, AMENDED/NATIVE – FREE OF ROCK AND DEBRIS
- ④ SHRUBBLER, 360 OR 180 SPIKE, 360 IN-LINE (ANTELCO).
- ⑤ 1/4" DISTRIBUTION TUBING VINYL (ANTELCO) LENGTH AS NEEDED.
- ⑥ JOINER 0.16", BARBxBARB, (ANTELCO) #40935 or #40145.
- ⑦ POLYETHYLENE PIPE, LLDPE. SIZE PER PLANS.
- ⑧ ASTA STAKE HOLD-DOWN #43615.

NOTE:
 SET ZONE PRESSURE TO 30
 PSI. ADJUST SHRUBBLER
 RADIUS AS NEEDED.

NOTE: ANTELCO SHRUBBLER SPIKE
 SPECIFICATIONS:

TYPE	ARC	MOD#	RAD.	GPH @	PSI
SPIKE	360° CIR	31495	1.5-FT	13.0 @	30
IN-LINE SPIKE	360° CIR	30995	1.5-FT	13.0 @	30
SPIKE	180° CIR	31295	2.0-FT	13.0 @	30

00

ANTELCO SHRUBBLER® SPIKE & IN-LINE SPIKE

N.T.S.

DETAIL-FILE