



NOTE:
 SET ZONE PRESSURE TO 30
 PSI. ADJUST VARI-ROTOR SPRAY
 DIAMETER AS NEEDED.

- ① FINISH GRADE OR TOP OF MULCH
- ② PLANT MATERIAL (SHRUB OR
 GROUND COVER)
- ③ CLEAN SOIL, AMENDED/NATIVE –
 FREE OF ROCK AND DEBRIS
- ④ VARI-ROTOR SPRAY 10-32 UNF
 THREAD (ANTELCO). MOUNT ON
 PVC RISER.
- ⑤ ADAPTER 1/2" FNPT x 10-32
 THREAD (ANTELCO) #41015.
- ⑥ LATERAL LINE PIPE, SEE PLAN
 FOR SIZE AND TYPE.
- ⑦ TEE/ELBOW, PVC SCH40, SIZE AS
 REQUIRED, SEE PLAN.
- ⑧ PVC SCH 80 RISER, THREADS
 BOTH ENDS, LENGTH AS NEEDED.

NOTE:

ANTELCO VARI-ROTOR SPRAY
 SPECIFICATIONS:

ARC	MOD#	DIAMETER	GPH	@	PSI
360°	CIR 20205	0-27-FT	0-33.0	@	30

00

ANTELCO VARI-ROTOR SPRAY™ ON PVC RISER

N.T.S.

DETAIL-FILE