

Putting Water Where it Counts!®



32 mm Fittings

www.antelco.com

32 mm Lateral Tube Fittings



A range of 32 mm fittings for low pressure irrigation and water systems. Used in conjunction with 32 mm I.D. low density polyethylene tubing.

Features

- Tapered entry on all barbed fittings for ease of installation.
- Operating pressure range up to 300 kPa.
- UV stabilised material for long field life.

Applications

Installations where 32 mm poly tube is required i.e. longer run lengths or higher volume systems.

FITTINGS



Joiner 32 mm

Joiners

Description	Order Code	Pack Qty.	Packs per Carton	Carton (kg)
Joiner 32 mm	44745	25	10	4.7
Reducing Joiner 32 mm x 25 mm	46095	25	12	4.6



Elbow 32 mm

Elbows

Description	Order Code	Pack Qty.	Packs per Carton	Carton (kg)
Elbow 32 mm	44825	25	8	5.1



Tee 32 mm

Tees

Description	Order Code	Pack Qty.	Packs per Carton	Carton (kg)
Tee 32 mm	45085	25	4	3.7
Reducing Tee 32 mm x 25 mm	45135	25	5	4.0



End Plug 32 mm

End Plugs

Description	Order Code	Pack Qty.	Packs per Carton	Carton (kg)
End Plug 32 mm	44585	25	16	5.7



Director 32 mm x 1" BSPM

Directors

Description	Order Code	Pack Qty.	Packs per Carton	Carton (kg)
Director 32 mm x 1" BSP Male Thread	45335	25	12	6.1

Antelco Australia
+61 8 8334 4333
adelaide@antelco.com.au

Antelco Europe
+44 152 585 9990
buzz@antelco.co.uk

Antelco USA
+1 407 331 0699
info@antelco.com

www.antelco.com

Ref : 32mmFITS_METRIC 200521