

32 mm LDPE Fittings



A range of 32 mm fittings for low pressure irrigation and water systems. Used in conjunction with 32 mm I.D. low density polyethylene tubing.

Features

- Tapered entry on all barbed fittings for ease of installation.
- Operating Pressure range up to 300 kPa.
- UV stabilised material for long field life.

Applications

Installations where 32 mm poly tube is required i.e. longer run lengths or higher volume systems.



Joiner 32 mm



Elbow 32 mm



Tee 32 mm



End Plug 32 mm



Director 32 mm x 1" BSPM

Joiners

Description	Order Code	Pack Qty.	Packs per Carton	Carton (kg)
Joiner 32 mm	44745	25	10	3.9
Reducing Joiner 32 mm x 25 mm	46095	25	12	3.8

Elbows

Description	Order Code	Pack Qty.	Packs per Carton	Carton (kg)
Elbow 32 mm	44825	25	8	4.3

Tees

Description	Order Code	Pack Qty.	Packs per Carton	Carton (kg)
Tee 32 mm	45085	25	4	2.9
Reducing Tee 32 mm x 25 mm	45135	25	5	3.2

End Plugs

Description	Order Code	Pack Qty.	Packs per Carton	Carton (kg)
End Plug 32 mm	44585	25	16	4.9

Directors

Description	Order Code	Pack Qty.	Packs per Carton	Carton (kg)
Director 32 mm x 1" BSPM	45335	25	12	5.3

Putting water where it counts !®

Antelco Group - Australia, USA, Europe
www.antelco.com