
Pinch Drip[™] Pressure Compensating Dripper





A high performance pressure compensating dripper with a sealed turbulent flow path and diaphragm to maintain uniform flow rates over a wide range of operating pressures. Low profile design to minimise risk of dislodgement from supply tubing and ergonomic finger grips for ease of installation.

Features

- Low manufacturing coefficient of variation (Cv) to provide high performance (conforms to ISO 9261).
- Three colour coded flow rates: 2 lph (Red), 4 lph (Black) & 8 lph (Green).
- Self-flushing cleaning action at low pressures.
- Insect baffle to reduce risk of blockages.
- Inlet barb has built-in filter.
- UV stabilised materials for long life.
- · Resistant to common agricultural chemicals & fertilisers.
- DripPets[®] 4 lph Pinch Drip[™] with eye catching Frog or Ladybug cover.


Applications

Vineyards, orchards, row crops and landscape.

Performance Chart

Pressure (kPa)	Flow (lph)		
riessule (Kra)	2 lph	4 lph	8 lph
50	2.1	3.4	5.7
100	2.3	4.1	7.2
150	2.3	4.4	7.4
200	2.4	4.6	7.6
250	2.4	4.6	7.7
300	2.3	4.6	7.5
350	2.2	4.5	7.3
MINIMUM FLOW PATH DIMENSION (mm)	0.7 x 0.6	0.8 x 0.8	1.2 x 0.9

Flow Rate



Ordering Information - Pinch Drip[™] PC

Description	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
2 lph Red Base	30705	100	85	10.1
4 lph Black Base	30715	100	85	10.1
8 lph Green Base	30725	100	85	10.1

Ordering Information - DripPets[®] 4 lph PC

Description	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
DripPets [®] Frog 4 lph	30815	100	18	7.7
Drippets [®] Ladybug 4 lph	30845	100	18	6.6

Specifications- Pinch Drip[™] PC

Dimensions Assembled		UV Stabilised Material		Base/Connection Type	
HEIGHT	25 mm	CAP	polypropylene		
WIDTH	28 mm	BASE	polypropylene	INLET	barb 4 mm
DEPTH	15 mm	DIAPHRAGM	silicone rubber	OUTLET	spout 4 mm
WEIGHT (approx.)	1.1g				





Pinch Drip[™] PC 8 lph Barb 4 mm

