



Spectrum™ 360° Adjustable Spray



An adjustable flow, full circle vortex sprayer with fine water droplets. Flow and coverage can be altered by rotating the cap.

Features

- Finger tip flow control with shut-off option.
- Spike model to anchor Spectrum™ at the plant.
- 4 mm barb model for direct attachment to micro or supply tubing.
- 4 mm thread for installation into Rigid Risers and Asta® Stakes or Micro Stakes.
- 1/2" thread for riser pipe installations.

Applications

Pots, tubs, ground cover, landscaped gardens and nurseries. Waters large garden areas when used with Asta® Stakes and Risers.

SPRAYS



Spectrum™ Spike
Inlet 4 mm



Spectrum™ Barb 4 mm



Spectrum™ Thread 4 mm




Spectrum™ Thread 1/2" Female


Performance Chart - Fully open (approx. 22 clicks)

Pressure (kPa)	360°	
	Flow (lph)	Diameter (m)
100	64	2.8
150	78	3.6
200	90	4.0

Flow Rate



Diameter of Throw



Ordering Information - Spectrum™ 360°

Base Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Barb 4 mm	32045	50	100	11.8
Thread 4 mm	32015	50	100	13.8
Thread 1/2" Female	32025	25	65	9.1
Spike	32095	25	40	6.9

Specifications

Dimensions Assembled		Barb	Thread	Thread 1/2"	Spike
HEIGHT		26 mm	26 mm	37 mm	137 mm
WIDTH		20 mm	20 mm	26 mm	42 mm
DEPTH		16 mm	16 mm	26 mm	16 mm
WEIGHT (approx.)		1.7 g	2.1 g	4.9 g	5.5 g
UV STABILISED MATERIAL	BASE	polypropylene	acetal	polypropylene	polypropylene
	CAP	polypropylene	polypropylene	polypropylene	polypropylene
	DEFLECTOR	acetal	acetal	acetal	acetal
BASE/CONNECTION TYPE: Inlet		barb 4 mm	thread 4 mm 10-32 UNF	thread 1/2" FNPT	barb 4 mm