



eZyvalve[®] 4



A compact valve box with 4 internal solenoid valves that connect to either a 24Vac or 9Vdc Latching irrigation controller. Installation is uncomplicated and the eZyvalve[®] 4 provides a trouble free way to distribute water to a micro irrigation system.

Features

- Pre-assembled with no internal pipe connections.
- High strength UV stabilised materials.
- Includes cable seal and wire connectors.
- Water, dust and pest resistant.
- Textured non-slip lid with o-ring seal and stainless steel screws.
- 3/4" BSPM threaded inlet and outlet connections.
- Easy to connect to existing garden taps using accessory Braided Hose.

Applications

Landscape, home gardens, greenhouses and nurseries. Above and below ground installation.

VALVES



eZyvalve[®] 4 - 24Vac



eZyvalve[®] 4 - 9Vdc Latching



Braided Hose



Performance Chart

Flow Rate (lpm)	Pressure Loss (kPa)
10	30
15	63
20	108
25	165
30	231

Ordering Information - eZyvalve[®] 4

Type	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
eZyvalve [®] 4 - 24Vac Solenoids 3/4" BSPM	16605	1	10	11.5
eZyvalve [®] 4 - 9Vdc Latching Solenoids 3/4" BSPM	16625	1	10	12.9

Ordering Information - Accessories

Type	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
Braided Hose 1000 mm x 3/4" BSPF	90603	1	40	16.1
Tap Adaptor 1" BSPF x 3/4" BSPM	45825	25	30	12.0

Specifications

Dimensions Packaged		Connection Type	
LENGTH	105 mm	Inlet:	3/4" BSPM tapered
DEPTH	182 mm		
WIDTH	182 mm		
WEIGHT (approx.) - 24 Vac	1075 g		
WEIGHT (approx.) - 9Vdc Latching	1150 g	Outlet:	3/4" BSPM parallel x 4

Operating Specifications

FLOW RANGE	1 lpm - 30 lpm
PRESSURE RANGE - 24 Vac	20 kPa - 1250 kPa
PRESSURE RANGE - 9 Vdc	20 kPa - 750 kPa
AMBIENT TEMPERATURE	2° C - 60° C
ELECTRICAL - 24 Vac	24 Vac, inrush current 320 mA, holding current 260 mA at 50 Hz
ELECTRICAL - 9 Vdc Latch	9 Vdc, inrush current 1200 mA