

Antelco Group of Companies

LINCOLN
— Est. 1959 —
MOULDING THE FUTURE

ANTELCO®



Putting Water Where it Counts!®



Antelco Australia
Antelco Pty Ltd ABN 50 008 062 708
Sales & Marketing,
Orders & Warehouse
Research & Development
PO Box 95, 131 Tolley Rd,
St Agnes SA 5097 Australia
+61 8 8334 4333
adelaide@antelco.com.au

Antelco USA
Antelco Corporation
Sales & Marketing,
Orders & Warehouse
886 Waterway Pl,
Longwood,
Florida 32750 USA
+1 407 331 0699
info@antelco.com

Antelco Europe
Antelco UK Limited
Sales & Marketing,
Orders & Warehouse
17a Chartmoor Rd,
Leighton Buzzard,
Bedfordshire LU7 4WG UK
+44 152 585 9990
orders@antelco.co.uk

eZyvalve™4

ALL IN ONE VALVE BOX WITH 4 VALVES

Made in Australia

antelco.com

eZyvalve™4

A compact valve box with 4 internal solenoid valves available in models to suit either 24 Vac or 9 Vdc latching irrigation controller. The eZyvalve™4 provides a trouble-free way to distribute water to micro irrigation systems and small to medium lawn areas.

Features

- Pre-assembled with no internal pipe connections.
- High strength UV stabilised materials.
- Includes cable seal and wire connectors.
- Water, dust and pest resistant.
- Textured non-slip lid with o-ring seal and stainless steel screws.
- 3/4" threaded inlet and outlet connections.
- Easy to connect to existing garden taps using Braided Hose accessory.

Performance Chart

Flow Rate (lpm)	Pressure Loss (kPa)
10	30
15	63
20	108
25	165
30	231

Ordering Information - eZyvalve™4

Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
eZyvalve™4 - 24 Vac Solenoids 3/4"	16605	1	10	11.5
eZyvalve™4 - 9 Vdc Latching Solenoids 3/4"	16625	1	10	12.9

Ordering Information - Accessories

Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Braided Hose 1000 mm x 3/4" BSPF	90603	1	40	16.1
Tap Adaptor 1" BSPF x 3/4" BSPM	45825	25	30	12.1

Ordering Information - Repair Kit

Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
eZyvalve™4 Diaphragm Kit	16604	1	125	-

Specifications

Dimensions Packaged	Connection Type
LENGTH 105 mm DEPTH 182 mm WIDTH 182 mm WEIGHT (approx.) - 24 Vac 1075 g WEIGHT (approx.) - 9 Vdc Latching 1150 g	INLET 3/4" BSPM tapered OUTLET 3/4" BSPM parallel x 4



Applications

Landscape, home gardens, lawn areas, greenhouses and nurseries. Above and below ground installation.

eZyvalve™4 - 24Vac

The eZyvalve™4 comes pre-assembled with no internal pipe connections for fast and easy DIY installation and is made from high strength UV stabilised materials.

The 24Vac model requires connection to a 24Vac irrigation controller.



Operating Specifications - 24Vac

FLOW RANGE	1 lpm -30 lpm
PRESSURE RANGE - 24 Vac	50 kPa - 750 kPa
AMBIENT TEMPERATURE	2° C - 60° C
ELECTRICAL - 24 Vac	24 Vac, inrush current 320 mA, holding current 260 mA at 50 Hz



eZyvalve™4 - 9Vdc

The eZyvalve™4 is a compact valve box with 4 internal solenoid valves designed to provide a trouble-free way to distribute water to a micro irrigation system. The 9Vdc model requires connection to a 4 station battery powered DC irrigation controller.

For non-potable water supply, a filtration device is recommended. Contact your local irrigation contractor / supplier for further advice.

When designing your irrigation system, refer to your local building codes for plumbing and electrical requirements.

Operating Specifications - 9Vdc

FLOW RANGE	1 lpm -30 lpm
PRESSURE RANGE - 9 Vdc	25 kPa - 750 kPa
AMBIENT TEMPERATURE	2° C - 60° C
ELECTRICAL - 9 Vdc	Latch 9 Vdc, inrush current 1200 mA



Tap Adaptor
1" BSPF x 3/4" BSPM
Code: 45825



Braided Hose
Code: 90603